

McKissick® Easy Reeve® Crane Blocks

#380 Series Easy Reeve® Hook Blocks

See Application and Warning Information on Pages 375 - 382 of the 2014 The Crosby Group Catalog.



The patented McKissick Split-Nut® is the standard retention system for standard crane blocks up to 100 tons.

Center "Dead End" to promote better travel under various reeving configurations.



Flat Bottom side plate for self standing during reeving process.

Sheave Guards that open to allow block reeving without removing the rope end fitting.

*Forged Crosby® alloy steel hooks with patented **QUIC-CHECK®** markings and Heavy Duty positive locking hook latch.*

Wide range of product available.

- Capacity: 5 to 80 tons - Larger Models Available.
- Sheave Sizes: 10" to 20".
- Wire Line Sizes: 7/16 to 1-1/4".
- Manufactured by an ISO 9001 and API QI certified facility.
- All single point shank hooks are genuine Crosby®, forged alloy steel, Quenched and Tempered, and have the patented QUIC-CHECK® markings (Duplex hooks are available on most sizes).
- All Easy Reeve® Blocks are furnished standard with Roller Bearings.
- Reeving Guides Standard -All Models.
- Blocks thru 25 tons use 319N hooks with S-4320 latches.
- Heavy Duty Positive Locking (PL) Latch-Models: 30 tons and larger.
- Sheave lubrication through center pin - Separate lube channel to each bearing.
- Sheaves fully protected by side plates.
- Dual action hook (Swings and Rotates).
- Repair parts available through world wide distribution network.
- Design Factor of 4:1 (unless otherwise noted).
- All Easy Reeve® blocks, 16" and larger, are furnished with McKissick® Roll-Forged™ sheaves with flame hardened grooves.
- Look for the Orange Hook... the mark of genuine McKissick® quality.

OPTIONS AVAILABLE:

- Duplex Hooks
- Swivel Tee and Shackle Assemblies
- Sheave Shrouds
- Anti Rotation-Locking Device
- Plate Steel Cheek Weights
- Third party testing with Certification available upon request.