



Western Manila Rope Blocks

Wood Blocks - Manila Rope



HS-21-B

- Laser cut side plates.
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with larger bearing diameter for extended block life.
- Becketts furnished on all blocks.
- For reeving information, see page 158.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability addressed by ASME B30.26.

Block Size (in.)	Fitting	Single Sheave 21 B Stock Number	Double Sheave 22 B Stock Number	Triple Sheave 23 B Stock Number
4	HS	603831	604634	605438
5	HS	603859	604652	605456
6	HS	603877	604670	605474
8	HS	603911	604714	605517
4	N	606437	606838	607230
5	N	606455	606856	607258
6	N	606473	606874	607276
8	N	606516	606918	607310
4	S	610039	611635	613232
5	S	610057	611653	613250
6	S	610075	611671	613278
8	S	610119	611715	613312

Block Size (in.)	Sheave Diameter (in.)			Manila Rope Size (in.)	Working Load Limit (lbs)*			Weight Each (lbs)		
	Outside Diameter	Rim Thickness	Center Pin Diameter		21 Single	22 Double	23 Triple	21 Single	22 Double	23 Triple
4	2.25	.63	.38	1/2	1000	1400	1800	1.75	3.00	4.00
5	3.00	.75	.38	5/8	1200	1800	2400	3.25	5.60	6.50
6	3.50	1.00	.50	3/4	1800	2500	3200	5.00	8.50	11.50
8	4.75	1.13	.63	7/8-1	2800	3800	4800	13.00	14.00	21.50

* Ultimate Load is 4 times the Working Load Limit.

Loose Side Hooks with Latch - Manila Rope

- Laser cut side plates.
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with larger bearing diameter for extended block life.

HS-262
Double



Block Size (in.)	Fitting	Manila Rope Size (in.)	Sheave Size		261 B Stock Number	262 B Stock Number	263 B Stock Number	Working Load Limit (lbs)*			Weight Each (lbs)		
			Outside Diameter (in.)	Rim Thickness (in.)				261 Single	262 Double	263 Triple	261 Single	262 Double	263 Triple
4	HS	1/2	2.25	.63	666826	666229	667228	900	1400	1800	1.38	3.21	3.25
5	HS	5/8	3.00	.75	666844	666247	-	1200	1800	-	2.25	3.88	-
6	HS	3/4	3.50	1.00	666862	666265	-	1800	2500	-	3.75	6.00	-
8	HS	7/8 - 1	4.75	1.13	666906	666309	667308	2800	3800	4800	7.13	10.75	14.75

* Ultimate Load is 3 time the Working Load Limit. Fitting Type: HS - Latch Hook.